

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 September 2005 (29.09.2005)

PCT

(10) International Publication Number
WO 2005/091256 A1

(51) International Patent Classification⁷: **G09F 7/02**

(74) Agent: **FOSTER, Shawn, F.**; Gardere Wynne Sewell LLP,
Suite 3400, 1000 Louisiana, Houston, TX 77002 (US).

(21) International Application Number:
PCT/US2005/009040

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 17 March 2005 (17.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/554,075 17 March 2004 (17.03.2004) US

(71) Applicant (*for all designated States except US*): **THE GIMPER GROUP, INC.** [US/US]; 3403 North Parkwood, Houston, TX 77021 (US).


(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **ROBERTS, Dwight** [US/US]; 3403 North Parkwood, Houston, TX 77021 (US).

[Continued on next page]

(54) Title: DEVICE FOR RETAINING A PLACARD WITHIN A PLACARD HOLDER, AND METHODS AND SYSTEMS THEREOF



(57) Abstract: A retaining device for improving the functionality of placard holders when the placard holder is subject to transient atmospheric conditions. The retaining device includes a member used in conjunction with a placard holder to more fully secure a placard with the placard holder when transient atmospheric conditions are encountered. The retaining device may be adapted to use with many designs of placard holders, including, but not limited to, U.S. Department of Transportation approved hazardous material information placard holders.

WO 2005/091256 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*